


MGS™ Speed Reducers

Best VALUE for your Industrial Gearing Needs



3 YEAR WARRANTY

STANDARD
3-DAY
DELIVERY



"we don't say we're best...our customers do"

www.stober.com

The **MGS**, or **Modular Gear System**, enables us to provide unprecedented service with full manufacturing, assembly, and support from our North American facility.

The **STOBER** difference = **VALUE** for you!

3 Rings

- Customer Service/Technical staff answers phone in 3 rings or less.

3 Days

- Standard – 3 day delivery
- Emergency – 24 hours, no expedite fee

3 Years (Warranty)

- Full 3 year warranty – all reducer components: gears, seals, bearings, covers, material and workmanship, etc.

High Efficiency

- Helical gears provide the highest efficiency possible in a geared unit. The following graph comparison shows combination units, helical/bevel (“K” Series) and helical/worm (“S” Series), versus a standard worm gear drive (competitor A).



Exceptional Performance

- Low Noise
- Cool Running
- High Speed Capacity
- High Torque Capacity
- One piece housings to prevent leaks

NEMA C-Face

- Choose any standard NEMA C-face motor

Dollar Savings Though:

- High efficiency saves energy cost
- Lubed for life saves maintenance cost
- 3 day delivery saves inventory cost
- 3 year warranty saves operating cost

Application Options

- Stainless steel hardware
 - Output shafts
 - Hollow output
 - Single or double side bushings
- Coatings
 - Standard severe duty gray paint
 - White washdown (FDA approved)
 - Stainless steel (FDA/USDA approved)

Additional Product Offering

- ComTrac™ Adjustable Speed Drives
- Food and Beverage Duty Speed Reducers
- Poultry Duty Speed Reducers
- ServoFit™ Precision Planetary Gearheads
- ServoFit™ Modular System Gearheads

MGSTTM Gear Drives. . . . always the solution.



Series "C"

Concentric/Helical Speed Reducers

- 1/6 to 165 HP
- Output torques to 62,000 in. lbs.
- Output speeds from 875 to 6.3 RPM
- Ratios from 2:1 to 276:1
- NEMA C-face or shaft input
- Foot or flange mounting

Series "F"

Offset/Helical Speed Reducers

- 1/6 to 33 HP
- Output torques to 9,743 in. lbs.
- Output speeds from 406 to 3 RPM
- Ratios from 4.3:1 to 552:1
- NEMA C-face or shaft input
- Output flange
- Solid, hollow, and wobble free bushing output



Series "K" – Right Angle

Helical/Bevel Speed Reducers

- 1/6 to 165 HP
- Output torques to 106,296 in. lbs.
- Output speeds from 437 to 4.5 RPM
- Ratios from 4:1 to 381:1
- NEMA C-face or shaft input
- Foot mount and output flange
- Solid (single or double), hollow, and wobble free bushing (single or double side) output



Series "S" – Right Angle

Helical/Worm Speed Reducers

- 1/6 to 8 HP
- Output torques to 7,086 in. lbs.
- Output speeds from 318 to 2.5 RPM
- Ratios from 9.2:1 to 683:1
- NEMA C-face or shaft input
- Foot mount and output flange
- Solid (single or double) and hollow output



A World of Solutions from a Local Source

STOBER drive systems are readily available around-the-world or around-the-corner from your local STOBER authorized distributors. You can depend on your STOBER distributor for the answers you need and the results you want.



STOBER Drives Inc.
Maysville, Kentucky



ServoFit™ SMS Gearheads



ComTrac™ Adjustable Speed Drives



STÖBER Antriebstechnik
Pforzheim, Germany

MGS™ Food, Beverage, and Poultry Duty



ServoFit™ Precision Planetary Gearheads

STOBER Drives, Inc.
1731 Downing Drive, Maysville KY 41056
Phone: 606 759-5090, FAX: 606 759-5045
Web: www.stober.com, E-mail: sales@stober.com

MGS™, Stober™, ComTrac™, and ServoFit™ are registered trademarks of STOBER Drives, Inc.
Form No. 3609, Copyright April, 2003, Printed in U.S.A.

